



# DL9300

## 24 WIRE DOT MATRIX PRINTER



- The DL9300 flatbed impact printer is a highly suitable solution for multipart continuous forms and cut sheet (max. eight copies including original), card stock and labels, meeting the full range of teller printing applications. You can print on almost anything.
- Standard APTC (Automatic Paper Thickness Control) and HCPP (Host-Controlled Paper Path) result in easy and fine print jobs, automatically.
- One of the quickest flat-bed impact printers, operating at 360 cps (draft quality, 10 cpi), the DL9300 saves valuable time in the office.
- Enhanced paper handling capability ensures flexibility.

### TECHNICAL SPECIFICATIONS

		DL9300
Print technology		24-Dot-Matrix
Max. resolution (HXV)		360 x 360dpi
Print speed	Letter	100cps (10cpi)
	Draft	360cps (10cpi)
Line feed speed		60ms at 6lpi
Paper feed speed		6ips
Command set		Fujitsu DPL24C Plus
Emulation		Epson LQ-1170, IBM Proprinter XL24E
Resident fonts	BITMAP	Courier 10, Pica 10, Prestige Elite 12, Boldface PS, OCR-A, OCR-B, Compression, Correspondence, Draft
	SCALABLE	Timeless, Courier, Nimbus-Sans
Character sets		IBM PC char. sets 1 and 2, IBM PS/2 char. sets (Codepage 437, 850, 851, 852, 855, 860, 862, 863, 865, 866), ISO8859-1/ECMA94 National character sets (USA, UK, German, French, Italian, Spanish, Swedish, Finnish, Norwegian, Danish 1 and 2, Hungarian 1 and 2, Slovenian 1 and 2, Mazowia 1 and 2, PG-DHN, Polish 1 and 2, Latin2 1 and 2, Latin P, ISO-Latin, Kamenicky 1 and 2, Turkish 1 and 2, ELOT927, ELOT928, Cyrillic, Lithuanian 1 and 2, Mik, Macedonian, PG-MAC, ABG, ABY, DEC, GR, Greek11, HBR-DEC and HBR-OLD) Bar code (Codabar, EAN8, EAN13, Code 3 of 9, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, UPC type A)
Print width (10 characters/inch)		80 characters, 203.2mm
Paper width	Fan-fold	102mm up to 267mm
	Out-sheet	55mm up to 267mm
Paper feed	Standard	Friction-feed platen, convertible bi-directional tractor on front and rear
	Optional	Single-bin cut sheet feeder for front and/or rear (common part) with envelope capability, convertible bi-directional tractor on front and/or rear (common part)
Copies		Max. 8 including original
Input buffer		Max. 96KB
Interface		Bi-directional Centronics plus RS232C
Weight		12.0kg
Noise level		54dBA
Power requirements		100VAC-120VAC +/- 10%, single-phase, 50/60Hz 220VAC-240VAC + 6% -10%, single-phase, 50/60Hz
Dimensions (H x W x D)		250 x 456 x 300mm
Lifetime	Black Ribbon	5 million characters
	Print head	300 million strokes each pin
MTBF		8000 hours at 25% duty cycle

## About Fujitsu

Fujitsu is a full service provider of information technology and communications solutions. Throughout Australia and New Zealand we partner with our customers to consult, design, build, operate and support business solutions. From strategic consulting to application and infrastructure solutions and services, Fujitsu has earned a reputation as the single supplier of choice for leading corporate and government organisations.

**Fujitsu Australia Limited** ABN  
19 001 011 427

**Fujitsu Australia Head Office**  
2 Julius Avenue North Ryde  
NSW 2113  
Telephone 61 2 9776 4555  
Facsimile 61 2 9776 4556

**Australian Capital Territory**  
10 Rudd Street  
Canberra ACT 2601  
Telephone 61 2 6212 6600  
Facsimile 61 2 6257 3798

**Northern Territory**  
79-81 Smith Street  
Darwin NT 0800  
Telephone 61 8 8943 7700  
Facsimile 61 8 8943 7777

**Queensland**  
1 Breakfast Creek Road  
Newstead Qld 4006  
Telephone 61 7 3119 3200  
Facsimile 61 7 3119 3211

**South Australia**  
99 Gawler Place  
Adelaide SA 5000  
Telephone 61 8 8305 8500  
Facsimile 61 8 8305 8555

**Victoria**  
1230 Nepean Highway  
Cheltenham Vic 3192  
Telephone 61 3 9265 0200  
Facsimile 61 3 9265 0500

**Western Australia**  
191 St George's Terrace  
Perth WA 6000  
Telephone 61 8 9212 5000  
Facsimile 61 8 9212 5111

**Fujitsu New Zealand Head Office**  
119-123 Featherston Street  
Wellington  
Telephone 64 4 495 0700  
Facsimile 64 4 495 0730

**Auckland**  
117 Khyber Pass Road  
Auckland  
Telephone 64 9 356 4800  
Facsimile 64 9 356 4851

**Christchurch**  
Unit 2 Amuri Park  
Cnr Bealey Avenue and  
Churchill Street  
Christchurch  
Telephone 64 3 353 4260  
Facsimile 64 3 363 4134

**au.fujitsu.com**  
**nz.fujitsu.com**

The Fujitsu logo consists of the word "FUJITSU" in a bold, sans-serif font. Above the letter "J" is a stylized infinity symbol (∞).

THE POSSIBILITIES ARE INFINITE