

# 9330N/ND Mono Laser Printer

## Transform Your Business

### Small and Efficient

Ideally suitable for workgroups or small networks, the feature rich 9330 mono laser printer will transform your documents increasing overall efficiency in your office. True 1200 dpi print quality coupled with a very respectable 28 page per minute A4 will ensure the 9330 range delivers professional quality output all within your budget.

### Choice of Models

The **9330N** offers two input paths, a 250 sheet cassette together with a 50 sheet multi-purpose feeder ideal for those non standard paper sizes. PCL and PostScript 3 is standard together with 64 Mb of onboard memory expandable to 320 Mb, will ensure the 9330N will speed through the most complex applications.

For duplex printing, the **9330ND** comes complete with its own built-in duplexer for hassle-free double sided printing on a wide variety of paper types and sizes. Both models can benefit from an additional optional 250 sheet cassette which can be simply installed by the user.

### Versatile

USB 2.0 connectivity is standard on all models for high use personal users together with Ethernet 10/100BaseT and parallel, making the 9330 the most versatile printers available today. PCL and PostScript together with a range of Windows driver setup utilities will ensure the 9330 will connect to virtually anything.



### Product Highlights:

- Up to 30 ppm letter 28 ppm A4
- Choice of models Simplex or Duplex
- Small and compact design
- 1200 x 1200 dpi print quality
- 8.5 Seconds first time to print
- Ideal for workgroups or small networks

# 9330N/ND Mono Laser Printer

---

<b>Print Speed</b>	Simplex (9330N): Up to 30 pages per minute letter, 28 pages per minute A4. Duplex (9330ND): Up to 21 pages per minute letter, up to 19 pages per minute A4
<b>Print Method</b>	Laser
<b>Processor</b>	SPGPm, 400MHz
<b>Resolution</b>	1200 x 1200 dpi
<b>Time To 1st Page</b>	First Page: Less than 8.5 seconds
<b>Memory</b>	64MB Standard, 320MB Maximum
<b>Standard Connectivity</b>	Parallel (Bi-directional IEEE 1284 compliant ECP/Nibble/Byte Mode), USB (v 2.0), Internal Ethernet (10BaseT & 100BaseTx); Automatic Interface Switching
<b>Standard Emulation</b>	PCL6 / PCL5e / IBM Proprinter / Epson PostScript Level 3 PDL / Barcode, Automatic Emulation Sensing
<b>Print Monitor</b>	SyncThru, SET IP
<b>Fonts</b>	1 Bit Map and 45 scaleable (35 Intellifont, 10 TrueType), 136 PS3 fonts

---

<b>Consumables</b>	High Yield: Replacement process unit 8,000 pages. Normal Yield: Replacement process unit 4,000 pages. Starter Process Unit Cartridge 4,000 pages. Based on 5% coverage of A4 page (ISO mSO/IEC 19752 TBA)
<b>STD Paper Handling</b>	Manual feed, 50 sheet multi-purpose feeder( MPF ) plus 250 sheet universal cassette
<b>Opt'l Paper Handling</b>	2nd universal cassette accepts 250 sheets
<b>Duplexing</b>	Automatic on 9330ND; Manual on 9330N (driver support provided)
<b>Paper Drive</b>	Envelope sizes: Monarch, No 9, No 10, C5, DL
<b>Paper Type</b>	MPF - paper, transparencies, labels, heavy paper stock, envelopes; Standard cassette - paper; Optional cassette - paper
<b>Paper Weight</b>	Cassette - 60-90gsm MPF - 60-163gsm Duplex 75-90gsm
<b>Paper Size</b>	MPF - A4, A5, A6, Letter, Legal, Folio, Executive, ISO B5, JIS B5, 3" x 5"; Standard Cassette - A4, A5, Letter Legal, Folio, Executive ISO B5, JIS, 3" x 5"; Optional Cassette - A4, A5, Letter, Legal, Folio, Executive ISO B5, JIS, 3" x 5"; Duplex - A4, Letter, Legal, Oficio, Folio
<b>Paper Output</b>	150 sheet face down, 1 sheet face up
<b>Printable Area</b>	Paper - 4mm from each side, 10 mm from top and bottom

---

<b>Physical Weight</b>	< 10.6kg including consumable
<b>PhysicalSize</b>	400(w) x 433(d) x 285(h) mm
<b>Power Voltage</b>	220-240V
<b>Power Frequency</b>	50/60Hz
<b>Power Consumption</b>	Less than 11 watts in sleep mode, Less than 900 watts printing (average)
<b>Compliance</b>	Energy Star Compliant
<b>Workload</b>	Up to 35,000 pages per month max, 4,000-7,000 per month average
<b>Reliability MTBF</b>	30,000 pages (Power on 8 hr/day in recommended duty cycle)
<b>Reliability MTTR</b>	30 minutes
<b>Drivers</b>	Windows 9.x/NT 4.0/2000/XP/ME/MAC, Posters, N-Up, Booklets, Duplex, Forms, Overlays, Watermarks
<b>Temperature</b>	10°C - 32°C (50°F - 89.6°F)
<b>Humidity</b>	10% - 80% relative humidity, non-condensing
<b>Altitude</b>	2,500 metres maximum
<b>Acoustic</b>	Printing - 54 dBA, Standby - 39 dBA, Sleepmode - Background Level
<b>Warranty</b>	2 years (Hot Swap)

---

**Option 1** 2nd cassette (250 sheet), 16/32/64/128Mb Memory

**Note** Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

---

**Available Configuration** **9330N** - Simplex model  
**9330ND** - Duplex model

---



Rutherford Road,  
Basingstoke,  
Hampshire RG24 8PD  
www.tallygenic.com.co.uk



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice. Copyright © 2007 TallyGenicom, L.P.

